



SYSTEM SPECIFICATIONS

Zoom: 2 - 14x

Lock Range: 400 Yards

Target

Velocity: 10 MPH

Calculated Target

Lock Time: .5 second

Tracking

Precision: 0.047 Minutes of

Angle (MOA, . 25 inches @ .3 miles)

RapidLok™

Trigger System: Proprietary trigger

system ensures accuracy by

acquiring, tracking and locking on ranged targets

Operating Time: 3.5 Hours

Batteries: (3) Dual Lithium

Ion Batteries

WiFi: 802.11G

Weather

Resistant: IP67 Splash, Water

& Dust Resistant

Weight: 11.4 lbs OAL: 36.25"

Compatible

With: ShotView™,

ShotGlass™, Night Vision, Thermal Attachments and Suppressors

Ammunition: TP 300 AAC BO

120 gr OTM; TP 300 AAC BO 120 gr Tac-TX; Any Quality 300 BO 110 gr

Reciever: 7075-T6 Forged

Aluminum; A3 Slick-Sided Upper

Barrel: 16" Light Contour

4150 ChromeMoly

Steel

5/8" x 24 Threaded .30 cal Muzzle Brake

Twist Rate: 1:7

Handguard: Midwest Industries™

M-Lok Full Length, Includes (3) 5-Slot

M-Lok Rails

ButtStock: TP Proprietary

Power

Enabled Adjustable

Stock

MODES

Suppressive Fire

Collects and holds real-time ballistics solution to systems maximum range. Trigger is live to reduce time to engagements.

Precision Targets

Calculates ballistic solution for stationary targets.

Precision Movers

Calculates firing solution for moving targets.

Auto-Acquire

User predesignates the tag on the target, allows for quick follow up shots to the same location.

Night Mode

For Gen-2, Gen-3, and Thermal attachments.

PACKAGE INCLUDES

(1) 10-Round Magazine BLK

(3) Batteries

(1) Battery Charger

(1) Pivot Bipod 6-9"

(1) Eye Guard, Shuttered