MISTAG ARMS

SYSTEM SPECIFICATIONS

Caliber: 5.56 NATO .223 Action: Semi-auto Direct Gas Impingement **Zoom:** 2 - 14x Lock Range: 600 Yards Target Velocity: 15 MPH Calculated Target Lock Time: .5 second Tracking Precision: 0.047 Minutes of Angle (MOA, .25 inches @ .3 miles) Ranging Capability: Integrated Laser Range Finder for targets at 600 yards RapidLok™ Trigger System: Proprietary trigger system ensures accuracy by acquiring, tracking and locking on ranged targets Weather Resistant: IP67 Splash, Water & Dust Resistant **Operating Time:** 3.5 Hours Batteries: Dual Lithium Ion Batteries

	802.11G
Compatible With:	ShotView [™] , ShotGlass [™] , Night Vision, Thermal Attachments and Suppressors
Ammunition:	Barnes 5.56 NATO 69gr OTM Barnes 5.56 NATO 70gr TSX Fort Scott 5.56 62gr UltraFlat
Barrel:	Stag Arms 16" 4150 Steel, ChromeLined, M4 profile, Manganese Phosphate, 1/2"x28 Threading
Twist Rate:	1:7
Muzzle:	A2 Flash Hider
Handguard:	Stag 15 13.5" M-LOK SL w/QD
ButtStock:	TP Proprietary Power Enabled Adjustable Stock
Weight:	12.2 lbs
OAL:	36.25"

SYSTEM TOTAL: \$9,995*

MODES

Suppressive Fire

Collects and holds real-time ballistics solution to systems maximum range. Trigger is live to reduce time to engagements.

Precision Targets

Calculates ballistic solution for stationary targets.

Precision Movers

Calculates firing solution for moving targets.

Auto-Acquire

User predesignates the tag on the target, allows for quick follow up shots to the same location.

Night Mode

For Gen-2, Gen-3, and Thermal attachments.



- (1) 10-Round Magazine BLK
- (3) Batteries
- (1) Eye Guard, Shuttered
- (1) Pivot Bipod 6-9"
- (1) Bipod Rail Adapter
- (1) Battery Charger

Next Generation of Precision Optics