











# SYSTEM SPECIFICATIONS

**Zoom:** 3 - 21x

1400 Yards

Target Velocity: 20 MPH

**Calculated Target** 

Lock Range:

Lock Time: 1 second

**Tracking Precision:** 0.047 Minutes of

Angle (MOA, .25 inches @ .3 miles)

Ranging Capability: Integrated Laser

Range Finder for targets at 1400 yards

RapidLok™

**Trigger System:** Proprietary trigger

system ensures accuracy by acquiring, tracking and locking on ranged targets

Operating Time: 3.5 Hours

Batteries: Dual Lithium Ion

Batteries

WiFi: 802.11G

Weather Resistant: IP67 Splash, Water & Dust Resistant

Compatible With: ShotView™,

ShotVlew , ShotGlass™, Night Vision,

Thermal Attachments and Suppressors

Ammunition: TP .338 LM 280 gr LRX

TP .338 LM 300 gr

OTM

Chassis: Proprietary Chassis

Barrel: 22" Stainless Steel

Shilen,

3/4" x 24 Threaded

Twist Rate: 1:10

**ButtStock:** TP Proprietary Power

Enabled Adjustable

Stock

Weight: 15.4 lbs

**OAL:** 39.25"

# **MODES**

#### **Precision Targets**

Calculates ballistic solution for stationary targets.

### **Precision Movers**

Calculates firing solution for moving targets.

### **Auto-Acquire**

User predesignates the tag on the target, allows for quick follow up shots to the same location.

## Suppressive Fire

Collects and holds real-time ballistics solution to systems maximum range. Trigger is live to reduce time to engagements.

### **Night Mode**

For Gen-2, Gen-3, and Thermal attachments.

# PACKAGE INCLUDES

(1) 5-Round Magazine BLK

(3) Batteries

(1) Battery Charger

**(1)** Eye Guard, Shuttered

(1) TP User Manual

(1) Harris-S

Model

Bipod 6" w/ DLOC-S and

SARG Knobs

